



SAF-T-STEP® Products

SQUEEZE-N-GO™

FLOOR SAFETY BURNISHING GEL

For Use On
Marble and Stone Floors and Over Acrylic Floor Finishes

PRODUCT FEATURES

- Floor remains dry
- Increases Slip Resistance
- Simple
- Great Shine
- Versatile
- Economical

USER BENEFITS

- Saves Time & Labor Cost
- Reduces Potential For Slip and Fall Accidents
- No Special Equipment or Procedures
- Protects Floor; Improves Appearance
- Use with Standard or High Speed Machines
- 1 Case Restores over 600,000 Sq. Ft.

DIRECTIONS FOR USE

1. Apply a 3 inch ribbon of SQUEEZE-N-GO™ to clean, restore, polish, protect and slip treat 1000-1250 sq. ft. of smooth floor surface.
2. Burnish with high speed burnish pad or equivalent; with standard speed machine use red or white polish pad.
3. Move to next floor section. Apply another 3 inch ribbon of SQUEEZE-N-GO™ and continue procedure until floor is complete.



Classified by Underwriters Laboratories Inc.®
as to Slip Resistance Only. 8L30

DYNAMIC

RESEARCH COMPANY, INC.

DISTRIBUTED BY:

DYNAMIC RESEARCH COMPANY, INC.

Safety Products Division

4800 SW Meadows Road - Suite 300

Lake Oswego, Oregon 97035

503-699-1335 FAX 503-699-1094

Order Desk: 800-876-2232

URL <http://www.saf-t-step.com>

SQUEEZE-N-GO™

FLOOR SAFETY BURNISHING GEL

Key Questions & Answers

What follows are the answers to the most often asked questions about Squeeze-N-Go™ Resistant Floor Cleaner & Treatment.

1. WHAT IS SQUEEZE-N-GO™?

ANSWER: Squeeze-N-Go™ is an Underwriters Laboratories® Floor Safety Treatment in a convenient thickened gel from which is used for raising the safety level (increasing the slip resistance) of the floor while enhancing the stone floor appearance or while restoring the gloss and extending finish life of acrylic floor finishes.

2. WHERE IS SQUEEZE-N-GO™ USED?

ANSWER: Squeeze-N-Go™ is commonly used with high speed floor burnishers to treat floor areas in schools, stores, and offices. Squeeze-N-Go™ eliminates the application and drying time needed for mop on and buff in restorers. It is effective when personnel or time limitations do not allow conventional restorer applications.

3. DO I NEED A SPECIAL FLOOR FINISH WITH SQUEEZE-N-GO™?

ANSWER: No. Squeeze-N-Go™ is designed to be used over stone floors and as a compliment to an existing floor finish program. Special finish, treatments, cleaners or polishing compounds are not required to achieve safer, beautiful looking floors.

4. WHAT COVERAGE WILL I GET WITH SQUEEZE-N-GO™?

ANSWER: Squeeze-N-Go™ is more economical than many of the restoring or burnishing products in the market place. When used as directed one case (6-16 oz squeeze bottles) of Squeeze-N-Go™ will burnish over 600,000 square feet of smooth floor surface.

5. WHAT IS THE RECOMMENDED APPLICATION PROCEDURE FOR USING SQUEEZE-N-GO™?

ANSWER: Dry mop floor prior to application of Squeeze-N-Go™. Heavier soiled areas, such as building entry areas, should be wet/damp mopped with a good neutral floor cleaner to remove dirt and particles that are detrimental to the long life of the floor finish.

6. HOW RESISTANT TO SCUFF MARKS IS SQUEEZE-N-GO™?

ANSWER: Squeeze-N-Go™ is harder than most of the floor finishes that are commonly used today and is very resistant to scuff marks and soiling.

7. DOES SQUEEZE-N-GO™ CONTAIN ZINC OR OTHER HEAVY METALS?

ANSWER: No. Squeeze-N-Go™ contains no zinc or other heavy metals and is an environmentally friendly product for use in those states, companies, or communities with heavy metal discharge concerns or limitations.

DYNAMIC

RESEARCH COMPANY, INC.

4800 SW Meadows Rd. Ste. 300 Lake Oswego, OR 97035
800-876-2232 503-699-1335 sales@saf-t-step.com www.saf-t-step.com