



SAF-T-STEP © Products

SQUEEZE-N-GO™

FLOOR SAFETY BURNISHING GEL

For Use On
Marble and Stone Floors and Over Acrylic Floor Finishes

PRODUCT FEATURES

- Floor remains dry
- Increases Slip Resistance
- Simple
- Great Shine
- Versatile
- Economical

USER BENEFITS

- Saves Time & Labor Cost
- Reduces Potential For Slip and Fall Accidents
- No Special Equipment or Procedures
- Protects Floor; Improves Appearance
- Use with Standard or High Speed Machines
- 1 Case Restores over 600,000 Sq. Ft.

DIRECTIONS FOR USE

1. Apply a 3 inch ribbon of SQUEEZE-N-GO™ to clean, restore, polish, protect and slip treat 1000-1250 sq. ft. of smooth floor surface.
2. Burnish with high speed burnish pad or equivalent; with standard speed machine use red or white polish pad.
3. Move to next floor section. Apply another 3 inch ribbon of SQUEEZE-N-GO™ and continue procedure until floor is complete.



Classified by Underwriters Laboratories Inc.®
as to Slip Resistance Only. 8L30

DYNAMIC

RESEARCH COMPANY, INC.

DISTRIBUTED BY:

DYNAMIC RESEARCH COMPANY, INC.

Safety Products Division

4800 SW Meadows Road - Suite 300

Lake Oswego, Oregon 97035

503-699-1335 FAX 503-699-1094

Order Desk: 800-876-2232

URL <http://www.saf-t-step.com>